

AGISEAL[®]

ELECTROSURGICAL GENERATOR

INTELLIGENT GENERATOR + REAL-TIME FEEDBACK TECHNOLOGY

SL100M



SL100M



Security and Reliable



Intelligent Feedback



Convenient Operation



[Vessel Sealing]



[Common Bipolar]

Four Key Features

- ▶ Real-Time Monitoring, Safe Operation
- ▶ Intelligent Regulation, Efficient Hemostasis
- ▶ Low-Temperature Protection, Favorable Prognosis
- ▶ Multi-Purpose Instrument, Convenient and Reliable

Generator Parameters

Weight	Depth	Width	Height
5 kg (11.02 lbs)	40 cm (15.75 in)	32.5 cm (12.8 in)	13 cm (5.12 in)

Operating Output Characteristics

Mode	Rated Load	Peak Voltage	Rated Output Power	Operating Frequency
Sealing	20Ω	287.5V	250W	472kHz ± 10%
Bipolar	100Ω	250V	95W	472kHz ± 10%

Nanjing ShouLiang-med Technology Co.,Ltd.

Tel: 025-58370102 Fax: 025-58370103

Block D9, No. 9 Kechuang Avenue, Intelligent Manufacturing Industrial Park (Zhihe Park), Jiangbei New Area, 211500 Nanjing City, Jiangsu Province, PEOPLE'S REPUBLIC OF CHINA

www.shouliangmed.com



✉ info@nj-soliang.com